

**General**

In-line four stroke diesel engine with direct injection. Rotation direction, anti-clockwise viewed towards flywheel.

Turbocharged

Number of cylinders			6
Displacement, total	litre		12,78
	in <sup>3</sup>		779,7
Firing order			1-5-3-6-2-4
Bore	mm		131
	in		5,16
Stroke	mm		158
	in		6,22
Compression ratio			18,1:1
Wet weight	Engine only	kg	1325
		lb	2921
	Engine incl. cooling system, air filtration system, and frame	kg	1790
		lb	3946

**Performance**

		rpm	1500	1800
Prime Power	without fan	kW	281	305
		hp	382	415
	with fan	kW	275	294
		hp	374	400
Standby Power	without fan	kW	308	335
		hp	419	456
	with fan	kW	302	324
		hp	411	441
Torque at:	Prime Power	Nm	1789	1618
		lbft	1319	1193
	Standby Power	Nm	1961	1777
		lbft	1446	1311
Mean piston speed		m/s	7,9	9,5
		ft/sec	26,0	31,2
Effective mean pressure at:	Prime Power	MPa	1,8	1,6
		psi	255	231
Effective mean pressure at:	Standby Power	MPa	1,9	1,7
		psi	280	254
Max combustion pressure at:	Prime Power	MPa	15,9	16,2
		psi	2306	2350
Max combustion pressure at:	Standby Power	MPa	17	16,7
		psi	2466	2422
Total mass moment of inertia, J (mR <sup>2</sup> )		kgm <sup>2</sup>	3,43	
		lbft <sup>2</sup>	81,4	
Friction Power		kW	30	44
		hp	40,8	59,84

**Derating see Technical Diagrams**

**Engine noise emission**

Test Standards: ISO 3744-1981 (E) sound power

Tolerance  $\pm 0.75$  dB(A)

		rpm	1500	1800
Measured sound power Lw	No load	dB(A)	112,8	115,2
	Prime Power	dB(A)	117,4	118,6
	Standby Power	dB(A)	117,9	119,1
Calculated sound pressure Lp at 1 m	No load	dB(A)	95,8	98,1
	Prime Power	dB(A)	100,3	101,6
	Standby Power	dB(A)	100,8	102,1

**Unsilenced exhaust noise**

Data calculated as sound pressure Lp.

Assumed microphone distance 1 m

	rpm	1500	1800
Prime Power	dB(A)	113	117
Standby Power	dB(A)	114	117

**Test conditions for load acceptance data**

Warm engine.	Generator	Model	Type of AVR
	Stamford	HCI 444 F1	SX 440

Load acceptance performance can vary due to actual alternator inertia, voltage regulator, type of load and local ambient conditions.

**Single step load performance at 1500 rpm**

Load (%)	Speed diff (%)		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	1,2	1,3	0,9	1,0	20-100	8,5	10,3	1,9	2,4
0-40	2,4	2,6	1,5	1,5	40-100	4,1	5,1	2,0	3,1
0-60	3,9	4,6	1,4	1,0	60-100	2,3	2,6	1,5	1,1
0-80	7,6	11,2	2,0	2,0	80-100	1,2	1,2	1,0	1,1
0-77	7,0		2,0		78-100	1,3		1,1	
0-86	10,0		2,0		87-100	0,8		0,9	
0-70		7,0		2,5	70-100		1,8		1,4
0-78		10,0		1,9	78-100		1,3		1,2
100-0	5,5	6,0	2,0	2,2					

**Single step load performance at 1800 rpm**

Load (%)	Speed diff %		Recovery time (s)		Remaining load (%)	Speed diff (%)		Recovery time (s)	
	Prime	Standby	Prime	Standby		Prime	Standby	Prime	Standby
0-20	1,1	1,3	1,0	1,2	20-100	4,5	5,0	1,1	2,5
0-40	2,2	2,5	1,4	1,4	40-100	2,8	3,5	1,5	1,7
0-60	3,4	3,8	1,5	1,6	60-100	1,7	1,9	1,5	1,7
0-80	4,7	5,6	1,4	1,3	80-100	0,9	0,9	1,2	1,4
0-85		6,0		1,1	85-100		1,0		1,4
0-100	7,0	10,0	1,5	2,2					
100-0	5,7	5,9	2,6	2,6					

**Cold start performance**

		°C	rpm	1500	1800
Time from start to stay within 0.5% of no load speed at ambient temperature:	20	s	4,8	4,6	
	5	s	5,7	5,2	
	-15*	s	6,6	6,0	

\* With manifold heater - kW engaged, lubrication oil 15W/40 and block heater.

Block heater type	Make	Power kW	Engaged hours	Cooling water temp engine block
	Volvo	2	12	10°C 50°F

**Lubrication system**

		rpm	1500	1800
Lubricating oil consumption	Prime Power	litre/h US gal/h	0,04 0,011	0,05 0,013
	Standby Power	litre/h US gal/h	0,04 0,011	0,05 0,013
Oil system capacity including filters		litre US gal	36 9,5	
Oil sump capacity:	max	litre US gal	30 7,9	
	min	litre US gal	19 5,0	
Oil change intervals/specifications:	VSD3	h	600	
	VSD2	h	400	
		h	200	
Engine angularity limits:	front up	°	11	
	front down	°	11	
	side tilt	°	11	
Oil pressure at rated speed		kPa psi	370 - 520 54 - 75	
Lubrication oil temperature in oil sump:	max	°C	130	
		°F	266	
Oil filter micron size		µ	40	

\* See also general section in the sales guide

**Fuel system**

		rpm	1500	1800
<b>Prime Power</b> Specific fuel consumption at:	25%	g/kWh lb/hph	230 0,373	237 0,384
	50%	g/kWh lb/hph	202 0,327	211 0,342
	75%	g/kWh lb/hph	195 0,316	202 0,327
	100%	g/kWh lb/hph	191 0,310	200 0,324
<b>Standby Power</b> Specific fuel consumption at:	25%	g/kWh lb/hph	226 0,366	242 0,392
	50%	g/kWh lb/hph	200 0,324	209 0,339
	75%	g/kWh lb/hph	194 0,314	201 0,326
	100%	g/kWh lb/hph	191 0,310	200 0,324

**VOLVO PENTA****TAD1341GE**

Document No

**21340719**

Issue Index

**02**

<b>Fuel system</b>	<b>rpm 1500 1800</b>		
Fuel to conform to	ASTM-D975-No1 and 2D JIS KK 2204, EN 590		
System supply flow at:	litre/h US gal/h	90,0 23,8	100,0 26,4
Fuel supply line max restriction (Measured at fuel inlet connection)	kPa psi	30,0 4,4	30,0 4,4
Fuel supply line max pressure, engine stopped	kPa psi	20,0 2,9	20,0 2,9
System return flow	litre/h US gal/h	18,0 4,8	18,0 4,8
Fuel return line max restriction (Measured at fuel return connection)	kPa psi	20,0 2,9	20,0 2,9
Maximum allowable inlet fuel temp (Measured at fuel inlet connection)	°C °F	50 122	50 122
Prefilter / Water separator micron size	µ	10	
Fuel filter micron size	µ	5	
Governor type/make, standard	Volvo / EMS 2.2		
Injection pump type/make	Delphi E3		

<b>Intake and exhaust system</b>		<b>rpm 1500 1800</b>		
Air consumption at: (+25°C and 100kPa)	Prime Power	m <sup>3</sup> /min cfm	22,7 802	26,4 932
	Standby Power	m <sup>3</sup> /min cfm	24,1 851	29 1024
Max allowable air intake restriction including piping		kPa psi	5 0,7	5 0,7
Air filter restriction clean Volvo Penta filter		kPa psi	0,7 0,1	0,9 0,1
Heat rejection to exhaust at:	Prime Power	kW BTU/min	187 10635	213 12113
	Standby Power	kW BTU/min	203 11544	235 13364
Exhaust gas temperature after turbine at:	Prime Power	°C °F	405 761	383 721
	Standby Power	°C °F	414 777	403 757
Max allowable back pressure in exhaust line	Prime Power	kPa psi	9 1,3	9 1,3
	Standby Power	kPa psi	10 1,5	10 1,5
Exhaust gas flow at: (temp and pressure after turbine at the corresponding power setting)	Prime Power	m <sup>3</sup> /min cfm	49,0 1730	58,0 2048
	Standby Power	m <sup>3</sup> /min cfm	52,0 1836	62,0 2190

**VOLVO PENTA****TAD1341GE**

Document No

**21340719**

Issue Index

**02****Cooling system**

			<b>rpm</b>	<b>1500</b>	<b>1800</b>
Heat rejection radiation from engine at:	Prime Power	kW		8	22
		BTU/min		455	1251
	Standby Power	kW		10	22
		BTU/min		569	1251
Heat rejection to coolant at:	Prime Power	kW		124	138
		BTU/min		7052	7848
	Standby Power	kW		133	148
		BTU/min		7564	8417
Coolant	Volvo Penta coolant "ready mix" or Volvo Penta coolant mixed with clean fresh water 40 / 60				
Radiator cooling system type	Closed circuit				
Standard radiator core area	m <sup>2</sup>		0,8		
	foot <sup>2</sup>		8,61		
Fan diameter	mm		890		
	in		35,04		
Fan power consumption	kW		6	11	
	hp		8	15	
Fan power consumption - Ratio 0,84:1	kW		6	11	
	hp		8	15	
Fan drive ratio	0,84 : 1				
Coolant capacity,	engine	litre	20		
		US gal	5,28		
	std radiator and hoses	litre	24		
		US gal	6,34		
Coolant pump	drive/ratio	Belt / 1,43 :1			
Coolant flow with standard system	l/s		5	5,5	
	US gal/s		1,32	1,45	
Minimum coolant flow	l/s		4,0	4,5	
	US gal/s		1,06	1,19	
Maximum outer circuit restriction, including piping	kPa		45	70	
	psi		6,5	10,2	
Thermostat	start to open	°C	82		
		°F	180		
	fully open	°C	92		
		°F	198		
Maximum static pressure head (expansion tank height + pressure cap setting)	kPa		100		
	psi		14,5		
Minimum static pressure head (expansion tank height + pressure cap setting)	kPa		70		
	psi		10,2		
Standard pressure cap setting	kPa		70		
	psi		10,2		
Maximum top tank temperature	°C		107		
	°F		225		
Draw down capacity. The difference between min coolant level in the expansion tank and the lowest level where the engine's coolant system still are functioning	litre		1,8		
	US gal		0,48		

**Charge air cooler system**

		<b>rpm</b>		
		<b>1500</b>		<b>1800</b>
Heat rejection to charge air cooler	Prime Power	kW	52	71
		BTU/min	2957	4038
	Standby Power	kW	59	80
		BTU/min	3355	4550
Charge air mass flow	Prime Power	kg/s	0,43	0,53
	Standby Power	kg/s	0,46	0,55
Charge air inlet temp. (Charge air temp after turbo compressor)	Prime Power	°C	165	184
		°F	329	363
	Standby Power	°C	176	197
		°F	349	387
Charge air outlet temp. (Charge air temp after intercooler)	Prime Power	°C	44	44
		°F	111	111
	Standby Power	°C	45	45
		°F	113	113
Maximum pressure drop over charge air cooler incl. piping		kPa	8	
		psi	1,16	
Charge air pressure (After charge air cooler)		kPa	203	
		psi	29,44	
Standard charge air cooler core area		m <sup>2</sup>	0,89	
		foot <sup>2</sup>	9,58	

**Cooling performance**

Cooling air flow and external restriction at different radiator air temperatures based on 107°C TTT and 40% coolant. Valid at 1 atm. (radiator and cooling fan, see optional equipment)

Engine speed rpm	Air on temp °C	PRIME POWER		STANDBY POWER	
		Air flow m <sup>3</sup> /s	External restriction Pa	Air flow m <sup>3</sup> /s	External restriction Pa
1500	55			4,4	315
	60	4,7	233	5,0	140
	63	5,1	115	5,5	0
	66	5,5	0		
1800	58			5,7	365
	60			6,4	132
	62			6,9	0
	64	5,6	425		
	66	6,9	0		

Note! External restrictions are calculated for values >0 Pa

**Engine management system**

Functionality	Alternatives	Default setting
Governor mode	Isochronus / Droop	Isochronus
Governor droop	0-8 %	0,0
Governor response	Adjustable PID-constants (VODIA)	Standard
Dual speed	YES	1500 or 1800
Idle speed	600-1200	900
Fine speed adjustment	± 120	0
Stop function	Energized to Run / Stop	Energized to Stop
Preheating function	On / Off	On
Lamp test	On / Off	On

**Engine sensor and switch settings**

Parameter	Unit	Alarm level		Engine protection		
		Setting range	Default setting	Level	Action. Default/Alternative	
Oil temp	°C	120 - 130	125	Setting +5	Shut down.	
Oil pressure	Low idle	kPa	-	190,0	-30,0	Shut down.
	1500 rpm	kPa	-	250,0	-30,0	Shut down.
	1800 rpm	kPa	-	300,0	-30,0	Shut down.
Oil level		-	Min level	-	-	
Piston cooling pressure >1000 rpm	kPa	-	150	150,0	Shut down.	
Coolant temp	°C	95 - 103	102	Setting +5	Shut down.	
Coolant level		See cooling system	On	Low level		
Fuel feed pressure	Low idle	kPa	-	100	-	-
	>1400 rpm		-	200	-	-
Water in fuel		-	High level	-	-	
Crank case pressure	kPa	-	Increased pressure	Increased pressure	Shut down.	
Air filter pressure droop	kPa	-	5	-	-	
	0,0		Alarm level		Engine protection	
Altitude, above sea	m	-	-	-	Automatic derating, see section derating	
Charge air temp	°C	-	80	85	Shut down.	
Charge air pressure	1500 rpm	kPa	-	360	370	Shut down.
	1800 rpm	kPa	-	350	360	Shut down.
Engine speed	rpm	100 - 120% of rated speed	120% of rated speed	Alarm level	Shut down.	

**Engine protection can be disabled. For consequences please see VP International Limited Warranty Policy**

**Electrical system**

Voltage and type		24V / insulated from earth	
Alternator:	make/output	A	Bosch 80 A
	tacho output	Hz/alt. Rev	6
	drive ratio		5,3:1
Starter motor	make	Melco	
	type	105P70	
	kW	7,0	
Number of teeth on:	flywheel	153	
	starter motor	12	
Max wiring resistance main circuit		mΩ	2
Cranking current at +20°C		A	180
Crank engine speed at 20°C		rpm	155
Starter motor battery capacity:	max	Ah/A	2x225
	min at +5°C	Ah/A	-
Inlet manifold heater (at 20 V)		kW	4,0
Power relay for the manifold heater		A	1

**Power take off****0 0 0**

Front end in line with crank shaft max:		Nm	-	
		lbft		
Front end belt pulley load. Direction of load viewed from flywheel side:	max left	kW	-	-
		hp		
	max down	kW	-	-
		hp		
Timing gear at compressor PTO max:		lbft	118	
Speed ratio direction of rotation viewed from flywheel side		0,91:1/clockwise		
Timing gear at servo pump PTO max:		Nm	100	
		lbft	74	
Speed ratio direction of rotation viewed from flywheel side		1,58:1/clockwise		
Timing gear at hydraulic pump PTO max:		Nm		
		lbft		
Speed ratio direction of rotation viewed from flywheel side				
Max allowed bending moment in flywheel housing		Nm	15000	
		lbft	11063	
Max. rear main bearing load		N	4000	
		lbf	899,2	